

GT



Technical data Luxura GT

Available colours :

Dark Bronze
DecoLight variant:
Blue, Red, Pink, Yellow

Pearl White
DecoLight variant:
Green, Blue, Red, Pink

VIP Gold
DecoLight variant:
Yellow, Blue

Classic Red
DecoLight variant:
White, Blue

Deep Yellow
DecoLight variant:
Blue

• = standard ◦ = Optional

- The 42 SLi, 42 SLi Int., 42 SLi H. Int., with 1.80 m tubes and shoulder-tanning feature available on request.
- CliMax only available in combination with ContourPlus
- Only available in combination with 1.80 m tubes in the bed.

| Type -> | 38 SLi | 38 SLi Intensive | 38 SLi High Intensive | 40 SPr | 40 SPr Intensive | 40 SPr High Intensive | 42 SLi | 42 SLi Intensive | 42 SLi High Intensive | 42 SLi IPControl |
|---|---------------------|---------------------|-----------------------|---------------------|---------------------|-----------------------|---------------------|---------------------|-----------------------|----------------------|
| Surface | Metallic | Metallic | Metallic | Metallic | Metallic | Metallic | Metallic | Metallic | Metallic | Metallic |
| Inside lighting | • | • | • | • | • | • | • | • | • | • |
| Tubes top | 22 x 100 W | 22 x 160 W | 22 x 160 W | 22 x 120 W | 22 x 180 W | 22x 180 W | 24 x 100 W | 24 x 160 W | 24 x 160 W | 24 x IP tubes 1.80 m |
| Tubes base | 16 x 100 W | 16 x 100 W | 16 x 160 W | 18 x 120 W | 18 x 120 W | 18 x 180 W | 18 x 120 W | 18 x 120 W | 18 x 180 W | 18 x IP tubes 2.00 m |
| Face tanner | 3 x 400 W | 3 x 400 W | 3 x 400 W | 23 x 25 W | 23 x 25 W | 23 x 25 W | 4 x 400 W | 4 x 400 W | 4 x 400 W | 4 x 400 W |
| Luxura Filter technology | • | • | • | – | – | – | • | • | • | • |
| HPS | ◦ | ◦ | ◦ | – | – | – | ◦ | ◦ | ◦ | ◦ |
| 2 m tubes in base ¹ | – | – | – | • | • | • | • | • | • | • |
| 5 steps adjustable body cooler | • | • | • | • | • | • | • | • | • | • |
| 5 steps adjustable face cooler | • | • | • | • | • | • | • | • | • | • |
| LED blower decor light | • | • | • | • | • | • | • | • | • | • |
| Decorative silver panel | • | • | • | • | • | • | • | • | • | • |
| Loudspeakers (2) | • | • | • | • | • | • | • | • | • | • |
| SoundAround including My MP3 | • | • | • | • | • | • | • | • | • | • |
| SmartVoice ² | | ◦ | ◦ | ◦ | ◦ | ◦ | ◦ | ◦ | ◦ | ◦ |
| ContourPlus | • | • | • | • | • | • | • | • | • | • |
| Xsens | ◦ | ◦ | ◦ | ◦ | ◦ | ◦ | ◦ | ◦ | ◦ | ◦ |
| Qsens | ◦ | ◦ | ◦ | ◦ | ◦ | ◦ | ◦ | ◦ | ◦ | ◦ |
| CliMax ² | ◦ | ◦ | ◦ | ◦ | ◦ | ◦ | ◦ | ◦ | ◦ | ◦ |
| BackFlex | • | • | • | ◦ ³ | ◦ ³ | ◦ ³ | ◦ ³ | ◦ ³ | ◦ ³ | ◦ ³ |
| Dust filters | • | • | • | • | • | • | • | • | • | • |
| EasyLift Acrylic system | • | • | • | • | • | • | • | • | • | • |
| Sound volume adjustment ² | • | • | • | • | • | • | • | • | • | • |
| LCD timer display | • | • | • | • | • | • | • | • | • | • |
| Programmable internal timer | • | • | • | • | • | • | • | • | • | • |
| Connection for external timer | • | • | • | • | • | • | • | • | • | • |
| Hour counter | • | • | • | • | • | • | • | • | • | • |
| 2nd hour counter with reset-function | • | • | • | • | • | • | • | • | • | • |
| Connection | 400 V -50 Hz 3~N/PE | 400 V -50 Hz 3~N/PE | 400 V -50 Hz 3~N/PE | 400 V -50 Hz 3~N/PE | 400 V -50 Hz 3~N/PE | 400 V -50 Hz 3~N/PE | 400 V -50 Hz 3~N/PE | 400 V -50 Hz 3~N/PE | 400 V -50 Hz 3~N/PE | 400 V -50 Hz 3~N/PE |
| Power (with CliMax) | ca. 6,3 (7,1) kW | ca. 7,6 (8,3) kW | ca. 9,3 (10,1) kW | ca. 5,8 (6,6) kW | ca. 7,4 (8,2) kW | ca. 8,5 (9,4) kW | ca. 7,2 (8,0) kW | ca. 9,0 (9,8) kW | ca. 10,2 (10,8) kW | ca. 9,4 (10,4) kW |
| Fuses | 3 x 16 A | 3 x 16 A | 3 x 16 A | 3 x 16 A | 3 x 16 A | 3 x 20 A | 3 x 16 A | 3 x 20 A | 3 x 20 A | 3 x 20 A |
| Weight (excl. packaging) (CliMax +50kg) | 285 kg | 305 kg | 325 kg | 295 kg | 315 kg | 330 kg | 305 kg | 325 kg | 340 kg | 285 kg |

